

4 MODULE ENCLOSURES 700 High/Low








SECTION A-A



8,







Module enclosure for M36 Din-rail. Series High-Low is, if requested with custom made holes for connectors and terminals. Lid, PCB, customized label and packing is available. Possibility for both base and top PCB. Aclosed version without terminals is also available. Trimmers and spindles that fit the hyeight of the box are available.

TECHNICAL DATA:

TOP PART: Material: Colour: Max. temperature: Width:

Label measurement: 41.0 x 66.0 mm Self-extinguishing: Acc. to UL94-V0 IP Protection: IP 20

BASE PART:

Material: Colour: Max. temperature: Max. load:


Terminals: Mounting: Self-extinguishing: Grey (RAL 7035) 100°C 70 mm (4 modules) 41.0 x 66.0 mm Acc. to UL94-V0 IP 20

Lexan 940

Noryl VO 1550 Black (RAL 9005) 100°C 16 A(for higher load please enquire) 24 fixed or plugable DIN-rail (EN50022) Acc. to UL94-V0

TYPE 700 High/low M4:	ORDER CODE
Complete, 257 for plugable	p/n 4979340702
Complete, 605 for fixed terminals	p/n 4979340701
Complete, closed, no terminals	p/n 4979340700
Top part, 257, plugable	p/n 4979330702
Top part, 605 / 250 fixed terminals	p/n 4979330701
Top part, grey, closed, no terminals	p/n 4979330700
Base part with clip and 2 screws	p/n 4969002701
DIN-rail clip for 700	p/n 0669000604
Transparent lid for 700	p/n 4969001700
Packing for 700	p/n 2068700001
Raw PCB for 700	p/n 4999000700
Terminal for 700, 257/12, HO/A, PCB part	p/n 1155712580
Terminal for 700, 256/12, wire part	p/n 1155612080
Terminal for 700, 605/12, fixed terminals	p/n 3950141208
Screw/selfcutting 2 pcs.	p/n 7006102965

HORIZONTAL PCB DIMENSIONS:



• All measurements are in mm.

• Please note that most plugable terminals are in 5,08 pitch and need a bigger hole in the PCB